

RECEIVED  
CENTRAL FAX CENTER

APR 03 2007

32692

Customer Number


Patent  
Case No.: 58460US002

## IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

First Named Inventor: VERNSTROM, GEORGE D.  
Application No.: 10/674594 Confirmation No.: 4487  
Filed: September 29, 2003 Group Art Unit 1745  
Title: FUEL CELL CATHODE CATALYST

BRIEF ON APPEAL

Mail Stop: Appeal Brief-Patents  
Commissioner for Patents  
P.O. Box 1450  
Alexandria, VA 22313-1450

CERTIFICATE OF MAILING OR TRANSMISSION [37 CFR § 1.8(n)]	
I hereby certify that this correspondence is being:	
<input type="checkbox"/>	deposited with the United States Postal Service on the date shown below with sufficient postage as first class mail in an envelope addressed to: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.
<input checked="" type="checkbox"/>	transmitted by facsimile on the date shown below to the United States Patent and Trademark Office at 571-273-8300.
April 3, 2007 Date	 Signed by: Phyllis Boettcher

Dear Sir:

This is an appeal from the Office Action mailed on July 3, 2006, in light of the Advisory Action mailed, finally rejecting claims 1-25.

- ☒ Please charge the fee provided in 37 CFR § 41.20(b)(2) to Deposit Account No. 13-3723. One copy of this sheet marked duplicate is also enclosed.
- ☐ Any required fee will be paid at the time of EFS-Web submission.
- ☒ If necessary, charge any required fee, or credit any overpayment to Deposit Account No. 13-3723.

A Notice of Appeal in this application was mailed on October 3, 2006, and was received in the USPTO on October 3, 2006.

BEST AVAILABLE COPY

32692

Customer Number

Duplicate

APR 03 2007

Patent  
Case No.: 58460US002

## IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

First Named Inventor: VERNSTROM, GEORGE D.  
Application No.: 10/674594 Confirmation No.: 4487  
Filed: September 29, 2003 Group Art Unit 1745  
Title: FUEL CELL CATHODE CATALYST


BRIEF ON APPEAL

Mail Stop: Appeal Brief-Patents  
Commissioner for Patents  
P.O. Box 1450  
Alexandria, VA 22313-1450

## CERTIFICATE OF MAILING OR TRANSMISSION [37 CFR § 1.8(a)]

I hereby certify that this correspondence is being:

- ☐ deposited with the United States Postal Service on the date shown below with sufficient postage as first class mail in an envelope addressed to: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.  
☒ transmitted by facsimile on the date shown below to the United States Patent and Trademark Office at 571-273-8300.

April 3, 2007  
Date  
Signed by: Phyllis Boettcher

Dear Sir:

This is an appeal from the Office Action mailed on July 3, 2006, in light of the Advisory Action mailed, finally rejecting claims 1-25.

- ☒ Please charge the fee provided in 37 CFR § 41.20(b)(2) to Deposit Account No. 13-3723. One copy of this sheet marked duplicate is also enclosed.  
☐ Any required fee will be paid at the time of EFS-Web submission.  
☒ If necessary, charge any required fee, or credit any overpayment to Deposit Account No. 13-3723.

A Notice of Appeal in this application was mailed on October 3, 2006, and was received in the USPTO on October 3, 2006.

Duplicate

APR 03 2007

Application No.: 10/674594

Case No.: 58460US002

**REAL PARTY IN INTEREST**

The real party in interest is 3M Company (formerly known as Minnesota Mining and Manufacturing Company) of St. Paul, Minnesota and its affiliate 3M Innovative Properties Company of St. Paul, Minnesota.

**RELATED APPEALS AND INTERFERENCES**

Appellants are unaware of any related appeals or interferences.

**STATUS OF CLAIMS**

Claims 1-25 are pending. Claims 1-25 stand rejected.

**STATUS OF AMENDMENTS**

No amendments have been filed after the final rejection.

**SUMMARY OF CLAIMED SUBJECT MATTER**

Independent claim 1 concerns a fuel cell cathode catalyst comprising nanostructured elements (defined in the Specification at page 3, lines 30-32) which comprise microstructured support whiskers (Specification at page 5, line 27 – page 6, line 6) bearing nanoscopic catalyst particles (defined in the Specification at page 4, lines 1-4). In the claims at issue, the nanoscopic catalyst particles are made by alternating application of first and second layers (Specification at page 6, line 7 – page 7, line 11), said first layer comprising platinum and said second layer being an alloy or intimate mixture of iron and a second metal selected from the group consisting of Group VIb metals, Group VIIb metals and Group VIIIb metals other than platinum and iron, where the atomic ratio of iron to said second metal in said second layer is between 0 and 10, where the planar equivalent thickness (defined in the Specification at page 4, lines 11-18) ratio of said first layer to said second layer is between 0.3 and 5, and wherein the average bilayer planar equivalent thickness (defined in the Specification at page 4, lines 19-21) of said first and second layers is less than 100 Å.

Independent claim 19 concerns a method of making a fuel cell cathode catalyst comprising nanoscopic catalyst particles (defined in the Specification at page 4, lines 1-4) comprising the alternate steps of vacuum deposition (Specification at page 6, line 22 – page 7,

APR 03 2007

Application No.: 10/674594

Case No.: 58460US002

line 11) of a first layer comprising platinum and vacuum deposition of a second layer comprising an alloy or intimate mixture of iron and a second metal selected from the group consisting of Group VIb metals, Group VIIb metals and Group VIIIb metals other than platinum and iron, where the atomic ratio of iron to said second metal in said second layer is between 0 and 10, wherein said deposited platinum and said deposited alloy or intimate mixture of two metals form a bilayer having an average bilayer planar equivalent thickness (defined in the Specification at page 4, lines 19-21) of less than 100 Å, wherein the planar equivalent thickness (defined in the Specification at page 4, lines 11-18) ratio of deposited platinum to the deposited alloy or intimate mixture of two metals is between 0.3 and 5.

#### GROUND OF REJECTION TO BE REVIEWED ON APPEAL

##### First Ground of Rejection

Claims 1-25 stand rejected under 35 U.S.C. § 103(a) as purportedly unpatentable over a single reference, U.S.Pat. No. 5,879,827 (Debe), taken alone.

#### ARGUMENT

##### First Ground of Rejection

Claims 1-25 stand rejected under 35 U.S.C. § 103(a) as purportedly unpatentable over a single reference, U.S.Pat. No. 5,879,827 (Debe), taken alone.

It is axiomatic that, in order to establish a prima facie case of obviousness of a claim, all the claim limitations must be taught or suggested by the prior art. In re Royka, 490 F.2d 981, 180 USPQ 580 (CCPA 1974); In re Wilson, 424 F.2d 1382, 1385, 165 USPQ 494, 496 (CCPA 1970)(cited at MPEP § 2143.03). In the present case, no prima facie case of obviousness have been established because the cited reference fails to teach or suggest claim limitations recited in the present claims.

Indeed, the Office Action recognizes numerous claim limitations recited in all of the present claims that are not taught in Debe (July 3 Office Action at pages 3 and 7-8), including:

--a first layer comprising platinum and said second layer being an alloy or intimate mixture of iron and a second metal selected from the group consisting of Group VIb metals, Group VIIb metals and Group VIIIb metals other than platinum and iron,

RECEIVED  
CENTRAL FAX CENTER

APR 03 2007

Application No.: 10/674594

Case No.: 58460US002

--where the atomic ratio of iron to said second metal in said second layer is between 0 and 10,

--where the planar equivalent thickness ratio of said first layer to said second layer is between 0.3 and 5, and

--wherein the average bilayer planar equivalent thickness of said first and second layers is less than 100 Å.

Claims 2-18 and 20-25 add additional features to independent claims 1 and 19, including features also not found in the single cited reference. Thus, claims 2-18 and 20-25 are patentable for those additional reasons.

The Examples of the present application (Specification at pages 7-14) include numerous demonstrations (Tables 1-8) of oxygen metric measurements for catalysts according to the present invention along with similar oxygen metric measurements for comparative catalysts (labeled "C"). The Examples demonstrate the distinct and superior performance exhibited by the catalysts according to the present invention.

Since no prima facie case of obviousness is made over this single reference, Applicants assert that the rejection of claims 1-25 under 35 U.S.C. § 103(a) should be reversed.

#### CONCLUSION

For the foregoing reasons, appellants respectfully submit that the Examiner has erred in rejecting this application. Please reverse the Examiner on all counts.

Respectfully submitted,

April 3, 2007

Date

By:



Philip Y. Dahl, Reg. No.: 36,115

Telephone No.: 651-737-4029

Office of Intellectual Property Counsel  
3M Innovative Properties Company  
Facsimile No.: 651-736-3833

APR 03 2007

Application No.: 10/674594

Case No.: 58460US002

CLAIMS APPENDIX

1. (Original) A fuel cell cathode catalyst comprising nanostructured elements which comprise microstructured support whiskers bearing nanoscopic catalyst particles, said nanoscopic catalyst particles made by alternating application of first and second layers, said first layer comprising platinum and said second layer being an alloy or intimate mixture of iron and a second metal selected from the group consisting of Group VIb metals, Group VIIb metals and Group VIIIb metals other than platinum and iron, where the atomic ratio of iron to said second metal in said second layer is between 0 and 10, where the planar equivalent thickness ratio of said first layer to said second layer is between 0.3 and 5, and wherein the average bilayer planar equivalent thickness of said first and second layers is less than 100 Å.
2. (Original) The fuel cell cathode catalyst according to claim 1 wherein the planar equivalent thickness ratio of said first layer to said second layer is between 0.3 and 2.5, and wherein the average bilayer planar equivalent thickness of said first and second layers is greater than 8 Å.
3. (Original) The fuel cell cathode catalyst according to claim 1 where the atomic ratio of iron to said second metal in said second layer is between 0.01 and 10.
4. (Original) The fuel cell cathode catalyst according to claim 1 wherein said second metal is selected from the group consisting of nickel, cobalt and manganese.
5. (Original) The fuel cell cathode catalyst according to claim 3 wherein said second metal is selected from the group consisting of nickel, cobalt and manganese.
6. (Original) The fuel cell cathode catalyst according to claim 1 wherein said second metal is nickel.
7. (Original) The fuel cell cathode catalyst according to claim 6 wherein the planar equivalent thickness ratio of said first layer to said second layer is between 0.3 and 2.5, and wherein the average bilayer planar equivalent thickness of said first and second layers is greater than 8 Å.

Application No.: 10/674594

Case No.: 58460US002

8. (Original) The fuel cell cathode catalyst according to claim 3 wherein said second metal is nickel.
9. (Original) The fuel cell cathode catalyst according to claim 8 wherein the atomic ratio of iron to nickel in said second layer is between 0.01 and 0.4.
10. (Original) The fuel cell cathode catalyst according to claim 8 wherein the atomic ratio of iron to nickel in said second layer is between 0.01 and 0.15.
11. (Original) The fuel cell cathode catalyst according to claim 1 wherein said second metal is cobalt.
12. (Original) The fuel cell cathode catalyst according to claim 11 wherein the planar equivalent thickness ratio of said first layer to said second layer is between 0.3 and 2.5, and wherein the average bilayer planar equivalent thickness of said first and second layers is greater than 8 Å.
13. (Original) The fuel cell cathode catalyst according to claim 3 wherein said second metal is cobalt.
14. (Original) The fuel cell cathode catalyst according to claim 13 wherein the planar equivalent thickness ratio of said first layer to said second layer is between 0.3 and 2, and wherein the average bilayer planar equivalent thickness of said first and second layers is greater than 8 Å.
15. (Original) The fuel cell cathode catalyst according to claim 1 wherein said second metal is manganese.
16. (Original) The fuel cell cathode catalyst according to claim 15 wherein the average bilayer planar equivalent thickness of said first and second layers is greater than 8 Å.
17. (Original) The fuel cell cathode catalyst according to claim 3 wherein said second metal is manganese.

Application No.: 10/674594

Case No.: 58460US002

18. (Original) The fuel cell cathode catalyst according to claim 17 wherein the planar equivalent thickness ratio of said first layer to said second layer is between 1.25 and 5.

19. (Original) A method of making a fuel cell cathode catalyst comprising nanoscopic catalyst particles comprising the alternate steps of vacuum deposition of a first layer comprising platinum and vacuum deposition of a second layer comprising an alloy or intimate mixture of iron and a second metal selected from the group consisting of Group VIb metals, Group VIIb metals and Group VIIIb metals other than platinum and iron, where the atomic ratio of iron to said second metal in said second layer is between 0 and 10, wherein said deposited platinum and said deposited alloy or intimate mixture of two metals form a bilayer having an average bilayer planar equivalent thickness of less than 100 Å, wherein the planar equivalent thickness ratio of deposited platinum to the deposited alloy or intimate mixture of two metals is between 0.3 and 5.

20. (Original) The method according to claim 19 wherein said vacuum deposition steps are carried out substantially in the absence of oxygen.

21. (Original) The method according to claim 19 wherein said platinum and said alloy or intimate mixture of iron and a second metal are deposited on microstructured support whiskers.

22. (Original) The method according to claim 19 wherein said second metal is selected from the group consisting of nickel, cobalt and manganese.

23. (Original) The method according to claim 19 wherein said second metal is nickel.

24. (Original) The method according to claim 19 additionally comprising the step of removing at least a portion of said alloy or intimate mixture of two metals after said deposition steps.

25. (Original) A fuel cell cathode catalyst comprising nanoscopic catalyst particles made according to the method of claim 23.



Application No.: 10/674394

Case No.: 58460US002

EVIDENCE APPENDIX

None.

Application No.: 10/674594

Case No.: 58460US002

**RELATED PROCEEDINGS APPENDIX**

None.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**